



EB200/EB201 Range

Cordless

Spot Sander



Paint Surface Sanding Expert

EB200 and EB201 range spot sanders are mainly used for spot sanding with PSA or VELCRO sandpaper, to repair paint defects, such as paint dust spots, particles, etc.

Brushless Motor

High-torque, long service life, excellent performance
Brushless for easy maintenance

6-Level Speed Setting

4000-10000/min for different purposes
With speed memory function, convenient and intelligent

Low Noise

Low noise provides a comfortable working environment

Lightweight Design

Slim and compact body, comfortable to hold, less fatigue for long time working

Universal Thread

Standard 1/4"-20 threaded backing plate, PSA or VELCRO mounting

Integrated Control Panel

Realize centralized management of power switch, power/load indicator, speed indicator, and speed control button.

Smart Load Indicator

Display battery charge and load status.

- Green: Sufficient battery charge/ light load
- Yellow: Medium battery charge/ medium load
- Red: Low battery charge/ heavy load



Two Models

(1) Orbital Spot Sander: EB200

- 3mm orbit, oscillation only(no spinning)

(2) Random Orbital Spot Sander: EB201

- Oscillation+spinning
- EB201-3: 3mm orbit, slight vibration, for small area sanding
- EB201-5: 5mm orbit, high efficiency, for fast sanding

10.8V

Li-ion Battery Pack

Powered by a lithium battery, no power cord constraint, prevents the power cord from scratching the paint surface, more convenient to use.

High-Performance Li-ion Battery For Long Running Time

With a 2.5Ah battery pack, work continuously for 40 minutes
With a 5.0Ah battery pack, work continuously for 80 minutes

*Test data of the machine under normal load.

Model	B1225A	B1250A
Capacity	2.5 Ah / 27.0 Wh	5.0 Ah / 54.0 Wh
Voltage	10.8 VDC	10.8 VDC
Weight	0.18 kg	0.38 kg
Overload Protection	√	√
Type	Rechargeable	Rechargeable
Continuous working time	2.5Ah: 40min	5.0Ah: 80min
Intermittent working time	2.5Ah: 1-2 days	5.0 Ah: 2-4 days



Fast Charger For continuous work



50-60 minutes to fully charge a 2.5Ah lithium battery pack
100-120 minutes to fully charge a 5.0Ah lithium battery pack
Use two battery packs together, ensure uninterrupted work.

*The charging time may vary depending on the state of the battery pack and environmental conditions

Model	BC121	BC122
Product	Single Bay Charger	Two-Bay Charger
Input	100-240 V~50/60Hz	100-240 V~50/60Hz
Output 1	10.8VDC, 3.0 Amp	10.8VDC, 3.0 Amp
Output 2		10.8VDC, 3.0 Amp
Rated Power	55W	80W
Weight	0.25 kg	0.56 kg
Charging Time	50-60 min(2.5Ah) 100-120 min(5.0Ah)	50-60 min(2.5Ah) 100-120 min(5.0Ah)

*BC122 supports simultaneous charging of two batteries.

Specification



Model	EB200	EB201-3	EB201-5
Product	Orbital Sander	Random Orbital Sander	Random Orbital Sander
Orbit Size	3mm	3mm	5mm
Motion	Oscillation only	Random orbit	Random orbit
Speed	4000-10000/min	4000-10000/min	4000-10000/min
Voltage	10.8VDC	10.8VDC	10.8VDC
Weight*	475g	495g	500g
Dimension	169X114.5X48.5mm	169X110.5X48.5mm	169X110.5X48.5mm
Thread	1/4"-20	1/4"-20	1/4"-20
Backing Plate	25mm, 31mm	25mm, 31mm	25mm, 31mm

*Tool only, no accessories or battery pack

Product Accessory Set:

31mm Backing plate(PSA, 1/4"-20) x 1

31mm Backing plate(Velcro, 1/4"-20) x 1

2500# Purple PSA pyramid sanding disc x 10

Battery pack(B1225A,2.5Ah) x 1

Single Bay charger(BC121) x 1



Follow Us: @shinemateofficial www.ShineMate.com

